

# TEHNOEXPORT

## TECHNICAL DUCTS



[www.tehnoexport.com](http://www.tehnoexport.com)



## DESCRIPTION AND APPLICATION

TEXOFLEX 1/22 duct is made of polyester fabric, both sides coated with self-extinguishing PVC reinforced with spiral high tension steel wire. Due to its exceptional flexibility can be easily installed on round and oval connectors. TEXOFLEX 1/22 is made for local extractions for workplaces, requiring safe handling of gases and dust.

🔥 **Application temperature:** from -25 °C to +70 °C

⊙ **Diameters:** from 82 mm to 356 mm

➔ **Lengths:** 3 m, 5 m, 10 m

# **Ar. Code:** TP + Color + 1/22 + diameter / length

🎨 **Color:** G-grey, B-blue, D-black, W-white

Internal diameter Ø=D / mm /	Name	Standard length / m /
82	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
90	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
102	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
112	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
120	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
127	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
133	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
140	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
152	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
165	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
185	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
203	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
229	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
254	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
280	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
305	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
315	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10
356	TEXOFLEX GREY 1/22 / BLUE 1/22 / BLACK 1/22 / WHITE 1/22	3 / 5 / 10



## DESCRIPTION AND APPLICATION

TEXOFLEX 2/22 duct is made of glass fabric, both sides coated with self-extinguishing PVC reinforced with spiral high tension steel wire. Due to its exceptional flexibility can be easily installed on round and oval connectors.

TEXOFLEX 2/22 is made for local extractions for workplaces of welding and galvanizing plants, hot air distribution, etc.

**Application temperature:** from -25 °C to +70 °C

**Diameters:** from 82 mm to 356 mm

**Lengths:** 3 m, 5 m, 10 m

**Ar. Code:** TP + Color + 2/22 + diameter/length

**Color:** G-grey, B-blue, D-black

Internal diameter Ø=D / mm /	Name	Standard length / m /
82	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
90	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
102	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
112	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
120	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
127	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
133	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
140	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
152	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
165	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
185	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
203	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
229	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
254	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
280	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
305	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
315	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10
356	TEXOFLEX GREY 2/22 / BLUE 2/22 / BLACK 2/22	3 / 5 / 10



## DESCRIPTION AND APPLICATION

TEXOFLEX ANTISTATIC PE-W is a lightweight flexible non-insulated duct, designed for local extractor for workplaces, requiring safe handling of gases and dust, etc. The duct is made of antistatic PE material reinforced with spiral high tension steel wire. Due to its exceptional flexibility can be easily installed on round and oval connectors. All the test based on antistatic properties should be done by customers.

 **Application temperature:** from -40 °C to +60 °C

 **Diameters:** from 102 mm to 203 mm

 **Lengths:** 3 m, 5 m, 7 m

 **Ar. Code:** ATPE-W + diameter / length

 **Color:** D-black

\* other lengths up on request

Internal diameter Ø=D / mm /	Name	Standard length / m /
102	TEXOFLEX ANTISTATIC PE-W	3 / 5 / 7
127	TEXOFLEX ANTISTATIC PE-W	3 / 5 / 7
165	TEXOFLEX ANTISTATIC PE-W	3 / 5 / 7
203	TEXOFLEX ANTISTATIC PE-W	3 / 5 / 7

\* other diameters up on request




## DESCRIPTION AND APPLICATION

TEXOFLEX ANTISTATIC PU-W is a lightweight flexible non-insulated duct, designed for local extractor for workplaces, requiring safe handling of gases and dust, etc. The duct is made of antistatic PU material reinforced with spiral high tension steel wire. TEXOFLEX ANTISTATIC PU-W duct has excellent resistance to abrasions. Due to its exceptional flexibility can be easily installed on round and oval connectors. All the test based on antistatic properties should be done by customers.

 **Application temperature :** from -40 °C to +90 °C

 **Diameters:** from 102 mm to 203 mm

 **Lengths:** 3 m, 5 m, 7 m

 **Ar. Code:** ATPU-W + diameter / length

 **Color:** D-black

\* other lengths up on request

Internal diameter Ø=D / mm /	Name	Standard length / m /
102	TEXOFLEX ANTISTATIC PU-W	3 / 5 / 7
127	TEXOFLEX ANTISTATIC PU-W	3 / 5 / 7
165	TEXOFLEX ANTISTATIC PU-W	3 / 5 / 7
203	TEXOFLEX ANTISTATIC PU-W	3 / 5 / 7

\* other diameters up on request





## DESCRIPTION AND APPLICATION


TEXOFLEX PU-W is a lightweight flexible non-insulated duct, made of PU material reinforced with spiral high tension steel wire. TEXOFLEX PU-W duct has excellent resistance to abrasions. Due to its exceptional flexibility can be easily installed on round and oval connectors. The duct is used for extractions in wood, metal, textile industries, etc.

 **Application temperature:** from -40 °C to +90 °C

 **Diameters:** from 60 mm to 356 mm

 **Lengths:** 3 m, 5 m, 10 m

 **Ar. Code:** TPU-W + diameter / length

 **Color:** transparent

\* other lengths up on request

Internal diameter Ø=D / mm /	Name	Standard length / m /
60	TEXOFLEX PU-W	3 / 5 / 10
76	TEXOFLEX PU-W	3 / 5 / 10
82	TEXOFLEX PU-W	3 / 5 / 10
90	TEXOFLEX PU-W	3 / 5 / 10
102	TEXOFLEX PU-W	3 / 5 / 10
112	TEXOFLEX PU-W	3 / 5 / 10
120	TEXOFLEX PU-W	3 / 5 / 10
127	TEXOFLEX PU-W	3 / 5 / 10
133	TEXOFLEX PU-W	3 / 5 / 10
140	TEXOFLEX PU-W	3 / 5 / 10
152	TEXOFLEX PU-W	3 / 5 / 10
165	TEXOFLEX PU-W	3 / 5 / 10
185	TEXOFLEX PU-W	3 / 5 / 10
203	TEXOFLEX PU-W	3 / 5 / 10
229	TEXOFLEX PU-W	3 / 5 / 10
254	TEXOFLEX PU-W	3 / 5 / 10
280	TEXOFLEX PU-W	3 / 5 / 10
305	TEXOFLEX PU-W	3 / 5 / 10
315	TEXOFLEX PU-W	3 / 5 / 10
356	TEXOFLEX PU-W	3 / 5 / 10





## DESCRIPTION AND APPLICATION

TEXOFLEX FDA is a lightweight flexible non-insulated duct, designed for local extractor for workplaces, requiring safe handling of gases and dust, etc. The duct is made of FDA approved material reinforced with spiral PVC coating high tension steel wire. Due to its exceptional flexibility can be easily installed on round and oval connectors. TEXOFLEX FDA is used for extractions in food and pharmaceutical industries.

 **Application temperature :** -10°C to +60°C

 **Diameters:** 160mm

 **Length:** 2m, 3m, 4m, 5 m

 **Ident:** TFDA+diameter/length

 **Color:** white

\* other lengths up on request

Internal diameter Ø=D / mm /	Name	Standard length / m /
160	TEXOFLEX FDA	2
160	TEXOFLEX FDA	3
160	TEXOFLEX FDA	4
160	TEXOFLEX FDA	5

\* other diameters up on request





## DESCRIPTION AND APPLICATION

TEXOFLEX PP is a lightweight flexible non-insulated duct, with smooth internal surface, made of PVC material reinforced with hard PVC spiral. Due to its exceptional flexibility can be easily installed on round and oval connectors.

The duct is used for suction and transport of dust and granular materials in wood, metal, plastic, textile industries, etc.

 **Application temperature :** from -10 °C to +60 °C

 **Diameters:** from 20 mm to 250 mm

 **Lengths:** 3 m, 5 m, 10 m, 20 m

**# Ar. Code:** TPP + diameter / length

 **Color:** white + transparent

Internal diameter Ø=D / mm /	Name	Standard length / m /
20	TEXOFLEX PP	3 / 5 / 10 / 20
22	TEXOFLEX PP	3 / 5 / 10 / 20
25	TEXOFLEX PP	3 / 5 / 10 / 20
28	TEXOFLEX PP	3 / 5 / 10 / 20
30	TEXOFLEX PP	3 / 5 / 10 / 20
35	TEXOFLEX PP	3 / 5 / 10 / 20
40	TEXOFLEX PP	3 / 5 / 10 / 20
45	TEXOFLEX PP	3 / 5 / 10 / 20
50	TEXOFLEX PP	3 / 5 / 10 / 20
52	TEXOFLEX PP	3 / 5 / 10 / 20
60	TEXOFLEX PP	3 / 5 / 10 / 20
63	TEXOFLEX PP	3 / 5 / 10 / 20
70	TEXOFLEX PP	3 / 5 / 10 / 20
75	TEXOFLEX PP	3 / 5 / 10 / 20
80	TEXOFLEX PP	3 / 5 / 10 / 20
90	TEXOFLEX PP	3 / 5 / 10 / 20
100	TEXOFLEX PP	3 / 5 / 10 / 20
110	TEXOFLEX PP	3 / 5 / 10 / 20
120	TEXOFLEX PP	3 / 5 / 10 / 20
125	TEXOFLEX PP	3 / 5 / 10 / 20
130	TEXOFLEX PP	3 / 5 / 10 / 20
140	TEXOFLEX PP	3 / 5 / 10 / 20
150	TEXOFLEX PP	3 / 5 / 10 / 20
160	TEXOFLEX PP	3 / 5 / 10 / 20
170	TEXOFLEX PP	3 / 5 / 10 / 20
180	TEXOFLEX PP	3 / 5 / 10 / 20
190	TEXOFLEX PP	3 / 5 / 10 / 20
200	TEXOFLEX PP	3 / 5 / 10 / 20
250	TEXOFLEX PP	3 / 5 / 10 / 20



## DESCRIPTION AND APPLICATION

TEXOFLEX PU is a lightweight flexible non-insulated duct, with smooth internal surface, made of PU material reinforced with hard PVC spiral. TEXOFLEX PU duct have excellent resistance to abrasion. Due to its exceptional flexibility can be easily installed on round and oval connectors. The duct is used for suction and transport of dust and granular materials in wood, metal, plastic, textile industries, etc.

 **Application temperature :** from -40 °C to +90 °C

 **Diameters:** from 20 mm to 250 mm

 **Lengths:** 3 m, 5 m, 10 m, 20 m

 **Ar. Code:** TPU + diameter / length

 **Color:** white + transparent

Internal diameter Ø=D / mm /	Name	Standard length / m /
20	TEXOFLEX PU	3 / 5 / 10 / 20
22	TEXOFLEX PU	3 / 5 / 10 / 20
25	TEXOFLEX PU	3 / 5 / 10 / 20
28	TEXOFLEX PU	3 / 5 / 10 / 20
30	TEXOFLEX PU	3 / 5 / 10 / 20
35	TEXOFLEX PU	3 / 5 / 10 / 20
40	TEXOFLEX PU	3 / 5 / 10 / 20
45	TEXOFLEX PU	3 / 5 / 10 / 20
50	TEXOFLEX PU	3 / 5 / 10 / 20
52	TEXOFLEX PU	3 / 5 / 10 / 20
60	TEXOFLEX PU	3 / 5 / 10 / 20
63	TEXOFLEX PU	3 / 5 / 10 / 20
70	TEXOFLEX PU	3 / 5 / 10 / 20
75	TEXOFLEX PU	3 / 5 / 10 / 20
80	TEXOFLEX PU	3 / 5 / 10 / 20
90	TEXOFLEX PU	3 / 5 / 10 / 20
100	TEXOFLEX PU	3 / 5 / 10 / 20
110	TEXOFLEX PU	3 / 5 / 10 / 20
120	TEXOFLEX PU	3 / 5 / 10 / 20
125	TEXOFLEX PU	3 / 5 / 10 / 20
130	TEXOFLEX PU	3 / 5 / 10 / 20
140	TEXOFLEX PU	3 / 5 / 10 / 20
150	TEXOFLEX PU	3 / 5 / 10 / 20
160	TEXOFLEX PU	3 / 5 / 10 / 20
170	TEXOFLEX PU	3 / 5 / 10 / 20
180	TEXOFLEX PU	3 / 5 / 10 / 20
190	TEXOFLEX PU	3 / 5 / 10 / 20
200	TEXOFLEX PU	3 / 5 / 10 / 20
250	TEXOFLEX PU	3 / 5 / 10 / 20

## ABOUT COMPANY

The company was established in 1953, as a family business and small workshop. The company changed its name to Tehnoexport in 1992.

Tehnoexport is now a leading manufacturer company of HVAC products and systems and sanitary equipment .

Tehnoexport produces a wide range of HVAC products, starting like semi-flexible aluminium ducts, pvc ducts, non-insulated laminated and insulated ducts. It also produces different types of sound attenuators and accessories.

In addition, we also produce sanitary equipment, with wide range of flexible siphons, floor drains and bathroom accessories.

Tehnoexport brand is well known for the quality of its products and prompt supplies, hence. This is confirmed by its involvement in prestigious projects all over the world.

Tehnoexport quality is internationally recognized thanks to its collaboration with important HVAC distributors; recently Tehnoexport decided to approach the international market independently, offering competitive commercial conditions. ndently, offering competitive commercial conditions.

The success of our company is due to the strong and innovative organizational approach and to our staff's international experience, professionalism and efficiency. The results achieved, only with the support of owners' capitals, are the base of our future operational and financial growth.

# TEHNOEXPORT

*The art of flexibility*

# TEHNOEXPORT

*The art of flexibility*

**address:** Jovana Popovica 43, 22320 Indjija, Serbia

**tel:** +381 22 553 453

**fax:** +381 22 561 417

**e-mail:** [office@tehnoexport.com](mailto:office@tehnoexport.com)

**web:** [www.tehnoexport.com](http://www.tehnoexport.com)