

TEHNOEXPORT



FLEKSIBILNE
VENTILACIONE CEVI

HVAC PROIZVODI
I SISTEMI

ALUTEX



Materijal: **AL/PET, Žica**
Ø82-508 mm/L: 10 m/T: od -30°C do +140°C
Konstrukcija: AP, APA, APP, AAAPP



POLYTEX



Materijal: **Met. PET, Žica**
Ø82-508 mm/L: 10 m/T: od -30°C do +120°C
Konstrukcija: MP-MP



TEXOFLEX COMBI



Materijal: **AL/PET, PVC, Žica**
Ø82-508 mm/L: 1,5;3;5;10 m/T: od -30°C do +140°C
Konstrukcija: APPVC, AAAPPVC



TEXOFLEX AL STRETCH



Materijal: **AL**
Ø80-400 mm/D: 1,5; 3; 5 m/T: od -30°C do +200°C
Konstrukcija: ALS



TEXOFLEX RF



Materijal: **INOX AISI 316 Ti**
Ø80-400 mm/L: 1; 2; 5 m/T: od -30°C do +450°C
Konstrukcija: RF, RFD (dupli zid)



TEXOFLEX WHITE PVC / GREY PVC



Materijal: **PVC, Žica**
Ø82-315 mm/D: 6; 10; 15 m/T: od -20°C do +70°C
Konstrukcija: PVC



TEXOFLEX WHITE 1



Materijal: **Poliestersko platno presvučeno PVC-om, Žica**
Ø82-635 mm/L: 1,5;3;5;10 m/T: od -25°C do +70°
Konstrukcija: Poliestersko platno presvučeno PVC-om



TEXOFLEX GREY 2



Materijal: **Stakleno platno presvučeno PVC-om, Žica**
Ø82-635 mm/L: 1,5;3;5;10 m/T: od -25°C do +70°C
Konstrukcija: Stakleno platno presvučeno PVC-om



IZOTEX



Materijal: **AL/PET, St. Vuna, Žica**
Ø82-508 mm/L: 10 m/T: od -30°C do +140°C
Konstrukcija: AP+SV+AP; APP+SV+APP



POLYTEX IZO



Materijal: **Met. PET, St. Vuna, Žica**
Ø82-508 mm/L: 10 m/T: od -30°C do +120°C
Konstrukcija: MP+SV+PMP



IZOTEX D



Materijal: **AL/PET, St. Vuna, Žica**
Ø82-457 mm/L: 5 m/T: od -30°C do +140°C
Konstrukcija: AAAPP+SV+AAAPP



POLYTEX IZO PVC



Materijal: **PVC, St. Vuna, Žica, PE**
Ø82-315 mm/L: 6; 10 m/T: od -30°C do +70°C
Konstrukcija: PVC+SV+PE



IZOTEX 1



Materijal: **Poliestersko platno presvučeno PVC-om, St. Vuna, PE, Žica**
Ø82-406 mm / L: 6; 10 m / T: from -20°C to +70°C
Konstrukcija: P+SV+PE



IZOTEX COMBI BLACK / GRAY



Materijal: **AL/PET, PVC, St. Vuna, Žica**
Ø82-406 mm/L: 10 m/T: od -30°C do +140°C
Konstrukcija: AP+SV+APPVC



SONOTEX



Materijal: **AL/PET, St. Vuna, Žica**
Ø82-508 mm/L: 10 m/T: od -30°C do +140°C
Konstrukcija: AP+SV+AP; APP+SV+APP



SONOTEX NW



Materijal: **Non Woven, AL/PET, St. Vuna, Žica**
Ø82-406 mm / D: 10 m/T: od -30°C do +140°C
Konstrukcija: SZ+SV+APP



TEXODAMP SONO



Materijal: **AL/PET, St. Vuna, Žica**
Ø82-406 mm/D: 0,5; 1; 1,5 m/T: od -30°C do +140°C
Konstrukcija: AP+SV+AP



TEXODAMP SONO NW



Materijal: **Non Woven, AL/PET, St. vuna, Žica**
Ø82-406 mm/L: 0,5; 1; 1,5 m/T: od -30°C do +140°C
Konstrukcija: NV+SV+APP



TEXODAMP BLACK / GRAY COMBI



Materijal: **PVC, AL/PET, St. Vuna, Žica**
 Ø82-406mm/L: 0,5; 1; 1,5 m/T: od -30°C do +140°C
 Konstrukcija: AAAPP+SV+APPVC



TEXO CONNECTOR AL STRECH



Materijal: **AL, INOX**
 Ø80-315 mm/L: 0,5; 1; 1,5 m/T: od -30°C do +250°C
 Konstrukcija: AL+INOX konektori



TEXO CONNECTOR ACU



Materijal: **AL, AL/PET, St. Vuna, INOX**
 Ø80-315 mm/L: 0,5; 1; 1,5 m/T: od -30°C do +140°C
 Construction: AL+SV+APP+INOX konektori



TEXO CONNECTOR ACU PE



Materijal: **AL, PE, St. Vuna, INOX**
 Ø80-315 mm/L: 0,5; 1; 1,5 m/T: od -30°C do +140°C
 Konstrukcija: AL+SV+PE+INOX konektori



TEXO CONNECTOR SONO



Materijal: **AL/PET, St. Vuna, INOX**
 Ø80-315 mm/L: 0,5; 1; 1,5 m/T: od -30°C do +140°C
 Konstrukcija: APP+SV+APP+INOX konektori



TEXO CONNECTOR NW



Materijal: **Non Woven, AL/PET, St. Vuna, INOX, Žica**
 Ø80-315 mm/L: 0,5; 1; 1,5 m/T: od -30°C do +140°C
 Konstrukcija: SZ+SV+APP+INOX konektori



TEXO CONNECTOR COMBI BLACK / GREY



Materijal: **PVC, AL/PET, St. Vuna, INOX, Žica**
 Ø80-315 mm/L: 0,5; 1; 1,5 m/T: od -30°C do +140°C
 Konstrukcija: AAAPP+SV+APPVC+INOX konektori



TEXODAMP SEMIRIGID



Materijal: **AL, St. Vuna**
 Ø80-315 mm/L: 0,5; 1 m/T: od -30°C do +250°C
 Konstrukcija: AL+SV+AL+AL konektori



TEXODAMP RIGID



Materijal: **Poc. Lim, St. Vuna, AL**
 Ø80-315 mm/L: 0,3; 0,6; 0,9 m/T: od -30°C do +250°C
 Konstrukcija: Poc. Lim+St. Vuna+Poc. Lim+AL priključci



TEXOFLEX SLEEVE / SLEEVE PE



Materijal: **AL/PET, St. Vuna**
 Ø82-508 mm/L: 10 m/T: od -30°C do +140°C
 Konstrukcija: APP+SV+PE+SV



TEXOFLEX WHITE/GRAY PVC RECTANGULAR



Materijal: **PVC, Žica**
 110x54-220x90 mm/L: 3; 6 m/T: od -20°C do +70°C
 Konstrukcija: PVC



IZOTEX ANTIMICROBIAL



Materijal: **AL/PET, St. Vuna, Žica**
 Ø82-508 mm/L: 10 m/T: od -30°C do +140°C
 Konstrukcija: APP+SV+APP, AAAPP+SV+APP



ALUTEX ANTIMICROBIAL



Materijal: **AL/PET, Žica**
 Ø82-508 mm/L: 10 m/T: od -30°C do +140°C
 Konstrukcija: APP, AAAPP



POLYTEX IZO PE



Materijal: **PE, St. Vuna, Žica**
 Ø82-508 mm/L: 10 m/T: od -30°C do +70°C
 Konstrukcija: PE+SV+PE



POLYTEX PE10



Materijal: **PE, Žica**
 Ø82-508 mm/L: 10 m/T: od -30°C do +70°C
 Konstrukcija: PE



TEXOFLEX JACKET



Materijal: **AL/PE, St. Vuna**
 Ø100-150 mm / T: od -30°C do +110°C
 Konstrukcija: AP+SV+AP



- Sistemi za ventilaciju
- Sistemi za klimatizaciju
- Smanjenje buke
- Za bolnice, škole, kancelarije
- Za mašine/ormane (npr. za pranje)
- Za pražnjenje sagorevanja



TEHNOEXPORT

The art of flexibility

adresa: Jovana Popovica 43, 22320 Indjija, Serbia

tel: +381 22 553 453

fax: +381 22 561 417

e-mail: office@tehnoexport.com

web: www.tehnoexport.com